

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1-5. (Cancelled).

6. (Currently Amended) An organic EL device, comprising:
 at least a first electrode layer, a light-emitting layer, and a second electrode layer ~~provided~~formed, in that order, above a substrate; and
 a first terminal that is connected to the first electrode layer and a second terminal ~~corresponding~~connected to the second electrode layer, which are formed above a same surface of the substrate as that above which the first electrode layer is ~~provided~~formed;
 wherein the second terminal and the second electrode layer are electrically ~~coupled with~~connected to each other ~~through~~by a conductive material which penetrates at least one intervening layer provided therebetween between the second terminal and the second electrode layer.

7. (Currently Amended) An electronic apparatus, comprising an organic EL device, the organic EL device further comprising:
 at least a first electrode layer;
 _____ a light-emitting layer; and
 _____ a second electrode layer formed, in that order, above a substrate;
 a first terminal connected to the first electrode layer and a second terminal ~~corresponding~~connected to the second electrode layer, which are formed above a same surface of the substrate as that above which the first electrode layer is ~~provided~~formed;
 wherein the second terminal and the second electrode layer are electrically ~~coupled with~~connected to each other ~~through~~by a conductive material which penetrates at

least one intervening layer provided therebetween between the second terminal and the second electrode layer.

8. (Currently Amended) An organic EL device, comprising:
- a first electrode formed on or over one surface of a substrate and connected to a first terminal;
 - a second electrode formed over the first electrode;
 - a light-emitting layer ~~provided~~formed between the first and the second electrode, in which a through hole is ~~provided~~formed;
 - a second terminal formed over the first electrode, at least a part of which faces to the second electrode via the through hole; and
 - a conductive material filled in the through hole and electrically connecting the second electrode and the second terminal.

9. (Previously Added) The organic EL device according to claim 8, the second electrode being formed on the conductive material and in contact thereto.

10. (Previously Added) The organic EL device according to claim 9, the second electrode having a plurality of layers, the bottom layer of which is in contact with the conductive material.

11. (Currently Amended) The organic EL device according to claim 10, the plurality of layers include a calcium layer and aluminum layer, and the calcium layer is in contact with the conductive ~~layer~~material.

12. (Cancelled).

13. (Currently Amended) The organic EL device according to claim 8, the conductive material including a material selected from a group consisting of ~~a~~-silver, ~~a~~-copper, ~~a~~-chromium, ~~a~~-nickel, ~~an~~-aluminum, ~~an~~-iron, ~~a~~-gold, ~~a~~-platinum, ~~a~~-carbon and a polymer with conductivity.

14. (Currently Amended) The organic EL device according to claim 8, the second electrode having the property of transparency.

15. (Currently Amended) The organic EL device according to claim 14, the conductive material including a material selected from a group consisting of an ITO, ~~a~~-gold, ~~a~~-silver, ~~a~~-copper, ~~a~~-calcium, ~~a~~-magnesium, ~~a~~-cesium, ~~a~~-strontium and ~~a~~-rubidium, and alloys composed of magnesium and ~~a~~-silver and of aluminum and ~~a~~-lithium.

16. (Previously Added) The organic EL device according to claim 15, the first electrode having no transparency.

17. (Previously Added) The organic EL device according to claim 8, a binder being provided in the through hole along with the conductive material.

18. (Currently Amended) The organic EL device according to claim 8, further comprising ~~ana~~ hole injection layer between the first and the second electrodes, the through hole being provided in the hole injection layer.